

**Trade name:** einza mix Solid Seidenglanzlack, Basis 1

**Product no.:** 0069184

**Current version :** 5.1.2, issued: 03.07.2023

**Replaced version:** 5.1.1, issued: 14.03.2023

**Region:** GB

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Trade name

**einza mix Solid Seidenglanzlack, Basis 1**

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses of the substance or mixture**

decorative paints/finishes

**Uses advised against**

No data available.

### 1.3 Details of the supplier of the safety data sheet

**Address**

einza Farben GmbH & Co KG

Junkersstraße 13

30179 Hannover

Telephone no. +49 (0)511 67490-0

Fax no. +49 (0)511 67490-20

e-mail [info@einza.com](mailto:info@einza.com)

**Advice on Safety Data Sheet**

[sdb\\_info@umco.de](mailto:sdb_info@umco.de)

### 1.4 Emergency telephone number

For medical advice (in German and English):

+49 (0)551 192 40 (Giftinformationszentrum Nord)

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Classification information**

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

This product does not meet the classification criteria given in the Regulation (EC) No 1272/2008 (CLP).

### 2.2 Label elements

**Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)**

**Hazard pictograms**

-

**Signal word**

-

**Hazard statement(s)**

-

**Hazard statements (EU)**

EUH210

Safety data sheet available on request.

EUH211

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

**Precautionary statement(s)**

-

**Labelling information**

The labelling (EU hazard statements) meets the criteria of annex II of Directive (EC) Nr. 1272/2008 (CLP).

Trade name: einza mix Solid Seidenglanzlack, Basis 1

Product no.: 0069184

Current version : 5.1.2, issued: 03.07.2023

Replaced version: 5.1.1, issued: 14.03.2023

Region: GB

### 2.3 Other hazards

PBT assessment

The components of this product are not considered to be a PBT.

vPvB assessment

The components of this product are not considered to be a vPvB.

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not applicable. The product is not a substance.

### 3.2 Mixtures

#### Hazardous ingredients

No	Substance name		Additional information	
	CAS / EC / Index / REACH no	Classification (EC) 1272/2008 (CLP)	Concentration	%
1	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]			
	13463-67-7 236-675-5 022-006-00-2 01-2119489379-17	Carc. 2; H351i	>= 25.00 - < 50.00	wt%
2	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics			
	- 918-481-9 - 01-2119457273-39	Asp. Tox. 1; H304 EUH066	>= 10.00 - < 25.00	wt%
3	propylidynetrimethanol			
	77-99-6 201-074-9 - 01-2119486799-10	Repr. 2; H361fd	< 0.50	wt%
4	silicon dioxide, chemically prepared			
	7631-86-9 231-545-4 - 01-2119379499-16	-	< 2.50	wt%

Full Text for all H-phrases and EUH-phrases: pls. see section 16

No	Note	Specific concentration limits	M-factor (acute)	M-factor (chronic)
1	V, W, 10	-	-	-

Full text for the notes: pls. see section 16 "Notes relating to the identification, classification and labelling of substances ((EC) No 1272/2008, Annex VI)".

No	Route, target organ, concrete effect
1	H351i inhalational; -; -

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### General information

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.

#### After inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

#### After skin contact

**Trade name:** einza mix Solid Seidenglanzlack, Basis 1

**Product no.:** 0069184

**Current version :** 5.1.2, issued: 03.07.2023

**Replaced version:** 5.1.1, issued: 14.03.2023

**Region:** GB

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

**After eye contact**

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

**After ingestion**

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

**4.2 Most important symptoms and effects, both acute and delayed**

No data available.

**4.3 Indication of any immediate medical attention and special treatment needed**

No data available.

## SECTION 5: Firefighting measures

**5.1 Extinguishing media**

**Suitable extinguishing media**

Alcohol resistant foam, CO<sub>2</sub>, powders, water spray

**Unsuitable extinguishing media**

water jet.

**5.2 Special hazards arising from the substance or mixture**

In the event of fire, the following can be released: Carbon monoxide (CO); Carbon dioxide (CO<sub>2</sub>); Toxic pyrolysis products; Exposure to decomposition products may cause a health hazard.

**5.3 Advice for firefighters**

Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses. Appropriate breathing apparatus may be required.

## SECTION 6: Accidental release measures

**6.1 Personal precautions, protective equipment and emergency procedures**

**For non-emergency personnel**

Exclude sources of ignition and ventilate the area. Avoid breathing vapours. Refer to protective measures listed in sections 7 and 8.

**For emergency responders**

No data available. Personal protective equipment (PPE) - see Section 8.

**6.2 Environmental precautions**

Is not allowed to be released into the sewerage or water courses. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

**6.3 Methods and material for containment and cleaning up**

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent - avoid use of solvents.

**6.4 Reference to other sections**

No data available.

## SECTION 7: Handling and storage

**7.1 Precautions for safe handling**

**Advice on safe handling**

**Trade name:** einza mix Solid Seidenglanzlack, Basis 1

**Product no.:** 0069184

**Current version :** 5.1.2, issued: 03.07.2023

**Replaced version:** 5.1.1, issued: 14.03.2023

**Region:** GB

Due to the organic solvents' content of the mixture: Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Avoid the inhalation of dust, particulates and spray mist arising from the application of this mixture. Dry sanding, flame cutting and/or welding of the dry paint film may give rise to dust and/or hazardous fumes. Wet [sanding]/[flattening] should be used wherever possible. Avoid inhalation of dust from sanding. For personal protection see section 8.

**General protective and hygiene measures**

Avoid skin and eye contact. Do not eat or drink during work - no smoking. Wash hands before breaks and after work. Clean skin thoroughly after work; apply skin cream.

**Advice on protection against fire and explosion**

Isolate from sources of heat, sparks and open flame. No sparking tools should be used. Electrical equipment should be protected to the appropriate standard. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

**7.2 Conditions for safe storage, including any incompatibilities**

**Technical measures and storage conditions**

Comply with legal health and safety regulations; Prevent unauthorised access. Keep container tightly closed and dry in a cool, well-ventilated place. Protect from heat and direct sunlight. Keep away from sources of ignition. No smoking.

**Requirements for storage rooms and vessels**

Always keep in containers of same material as the original one. Never use pressure to empty: container is not a pressure vessel. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed. Observe label precautions.

**Incompatible products**

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

**7.3 Specific end use(s)**

No data available.

**SECTION 8: Exposure controls/personal protection**

**8.1 Control parameters**

**Occupational exposure limit values**

No	Substance name	CAS no.	EC no.
1	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	13463-67-7	236-675-5
<b>List of approved workplace exposure limits (WELs) / EH40</b>			
Titanium dioxide			
total inhalable dust			
	WEL long-term (8-hr TWA reference period)	10	mg/m <sup>3</sup>
<b>List of approved workplace exposure limits (WELs) / EH40</b>			
Titanium dioxide			
respirable dust			
	WEL long-term (8-hr TWA reference period)	4	mg/m <sup>3</sup>
2	silicon dioxide, chemically prepared	7631-86-9	231-545-4
<b>List of approved workplace exposure limits (WELs) / EH40</b>			
Silica, amorphous inhalable dust			
	WEL long-term (8-hr TWA reference period)	6	mg/m <sup>3</sup>
<b>List of approved workplace exposure limits (WELs) / EH40</b>			
Silica, amorphous respirable dust			
	WEL long-term (8-hr TWA reference period)	2.4	mg/m <sup>3</sup>

**DNEL, DMEL and PNEC values**

**DNEL values (worker)**

No	Substance name	CAS / EC no		
	Route of exposure	Exposure time	Effect	Value
1	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	13463-67-7 236-675-5		

**Trade name:** einza mix Solid Seidenglanzlack, Basis 1

**Product no.:** 0069184

**Current version :** 5.1.2, issued: 03.07.2023

**Replaced version:** 5.1.1, issued: 14.03.2023

**Region:** GB

	inhalative	Long term (chronic)	local	1.25	mg/m <sup>3</sup>
2	<b>propylidynetrimethanol</b>			<b>77-99-6</b> <b>201-074-9</b>	
	dermal	Long term (chronic)	systemic	0.94	mg/kg/day
	inhalative	Long term (chronic)	systemic	3.30	mg/m <sup>3</sup>

**DNEL value (consumer)**

No	Substance name			CAS / EC no	
	Route of exposure	Exposure time	Effect	Value	
1	<b>titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]</b>			<b>13463-67-7</b> <b>236-675-5</b>	
	inhalative	Long term (chronic)	local	210	µg/m <sup>3</sup>
2	<b>propylidynetrimethanol</b>			<b>77-99-6</b> <b>201-074-9</b>	
	oral	Long term (chronic)	systemic	0.34	mg/kg/day
	dermal	Long term (chronic)	systemic	0.34	mg/kg/day
	inhalative	Long term (chronic)	systemic	0.58	mg/m <sup>3</sup>

## 8.2 Exposure controls

### Appropriate engineering controls

Provide good ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

### Personal protective equipment

#### Respiratory protection

If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators. When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits. In case of brush application: Filter A2. When applied by spraying: Filter A2P2. (DIN EN 14387)

#### Eye / face protection

Wear safety goggles to protect against splashes. Safety glasses with side protection shield (EN 166)

#### Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Appropriate Material In case of short-term contact / splash protection: nitrile rubber

Material thickness > 0.4 mm

Breakthrough time > 120 min

Appropriate Material In case of prolonged exposure: nitrile rubber

Material thickness > 0.4 mm

Breakthrough time > 480 min

#### Other

Personnel should wear anti-static clothing made of natural fibre or of high temperature resistant synthetic fibre.

#### Environmental exposure controls

Do not allow to enter drains or water courses.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

<b>State of aggregation</b>
liquid
<b>Form</b>
liquid

# EU safety data sheet



**Trade name:** einza mix Solid Seidenglanzlack, Basis 1

**Product no.:** 0069184

**Current version :** 5.1.2, issued: 03.07.2023

**Replaced version:** 5.1.1, issued: 14.03.2023

**Region:** GB

<b>Colour</b>			
according to product name			
<b>Odour</b>			
characteristic			
<b>pH value</b>			
No data available			
<b>Boiling point / boiling range</b>			
Value	appr.	100	°C
<b>Melting point/freezing point</b>			
No data available			
<b>Decomposition temperature</b>			
No data available			
<b>Flash point</b>			
Value	>=	62	°C
Method	closed cup		
<b>Ignition temperature</b>			
No data available			
<b>Oxidising properties</b>			
Not applicable			
<b>Flammability</b>			
Not applicable			
<b>Lower explosion limit</b>			
No data available			
<b>Upper explosion limit</b>			
No data available			
<b>Vapour pressure</b>			
Value	<	100	hPa
Reference temperature		50	°C
<b>Relative vapour density</b>			
No data available			
<b>Relative density</b>			
No data available			
<b>Density</b>			
Value	0.94	-	1.29 g/cm <sup>3</sup>
Reference temperature			20 °C
Method	DIN 51757		
<b>Solubility in water</b>			
Comments	immiscible		
<b>Solubility</b>			
No data available			
<b>Partition coefficient n-octanol/water (log value)</b>			
No	Substance name	CAS no.	EC no.
1	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	13463-67-7	236-675-5
Not applicable			
Source		ECHA	
2	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	-	918-481-9
log Pow	3.17	-	7.22

Trade name: einza mix Solid Seidenglanzlack, Basis 1

Product no.: 0069184

Current version : 5.1.2, issued: 03.07.2023

Replaced version: 5.1.1, issued: 14.03.2023

Region: GB

Method	QSAR		
Source	ECHA		
<b>3</b>	<b>propylidyntrimethanol</b>	<b>77-99-6</b>	<b>201-074-9</b>
log Pow		-0.47	
Reference temperature		26	°C
Method	OECD		
Source	ECHA		

<b>Kinematic viscosity</b>			
Value	55	- 60	sec
Reference temperature		20	°C
Method	DIN EN 2431 (6 mm)		

<b>Solvent separation test</b>			
Not applicable			

<b>Particle characteristics</b>			
No data available			

## 9.2 Other information

<b>Other information</b>			
No data available.			

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Stable under recommended storage and handling conditions (See section 7).

### 10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

### 10.3 Possibility of hazardous reactions

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

### 10.4 Conditions to avoid

Heat, naked flames and other ignition sources.

### 10.5 Incompatible materials

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

### 10.6 Hazardous decomposition products

None if stored, handled and transported properly. In case of fire: see section 5.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

<b>Acute oral toxicity</b>			
No	Substance name	CAS no.	EC no.
<b>1</b>	<b>titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]</b>	<b>13463-67-7</b>	<b>236-675-5</b>
LD50	>	2000	mg/kg bodyweight
Species	rat		
Method	OECD 401		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
<b>2</b>	<b>Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, &lt;2% aromatics</b>	<b>-</b>	<b>918-481-9</b>
LD50	>	15000	mg/kg bodyweight
Species	rat		
Method	OECD 401		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
<b>3</b>	<b>propylidyntrimethanol</b>	<b>77-99-6</b>	<b>201-074-9</b>

**Trade name:** einza mix Solid Seidenglanzlack, Basis 1

**Product no.:** 0069184

**Current version :** 5.1.2, issued: 03.07.2023

**Replaced version:** 5.1.1, issued: 14.03.2023

**Region:** GB

LD50	14700	mg/kg bodyweight
Species	rat	
Source	ECHA	

Acute dermal toxicity			
No	Substance name	CAS no.	EC no.
1	propylidynetrimethanol	77-99-6	201-074-9
LD50	>	10000	mg/kg bodyweight
Species	rabbit		
Source	ECHA		

Acute inhalational toxicity			
No	Substance name	CAS no.	EC no.
1	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	13463-67-7	236-675-5
LC50		5.09	mg/l
Duration of exposure		4	h
State of aggregation	Dust		
Species	rat		
Method	OECD 403		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Skin corrosion/irritation			
No	Substance name	CAS no.	EC no.
1	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	13463-67-7	236-675-5
Species	rabbit		
Method	OECD 404		
Source	ECHA		
Evaluation	non-irritant		
Evaluation/classification	Based on available data, the classification criteria are not met.		
2	propylidynetrimethanol	77-99-6	201-074-9
Species	rabbit		
Source	ECHA		
Evaluation	non-irritant		

Serious eye damage/irritation			
No	Substance name	CAS no.	EC no.
1	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	13463-67-7	236-675-5
Species	rabbit		
Method	OECD 405		
Source	ECHA		
Evaluation	non-irritant		
Evaluation/classification	Based on available data, the classification criteria are not met.		
2	propylidynetrimethanol	77-99-6	201-074-9
Species	rabbit		
Source	ECHA		
Evaluation	non-irritant		

Respiratory or skin sensitisation			
No	Substance name	CAS no.	EC no.
1	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	13463-67-7	236-675-5
Route of exposure	Skin		
Species	mouse		
Method	OECD 429		
Source	ECHA		
Evaluation	non-sensitizing		



**Trade name:** einza mix Solid Seidenglanzlack, Basis 1

**Product no.:** 0069184

**Current version :** 5.1.2, issued: 03.07.2023

**Replaced version:** 5.1.1, issued: 14.03.2023

**Region:** GB

Evaluation/classification	Based on available data, the classification criteria are not met.		
<b>2</b>	<b>propylidynetrimethanol</b>	<b>77-99-6</b>	<b>201-074-9</b>
Route of exposure	Skin		
Species	mouse		
Method	OECD 429		
Source	ECHA		
Evaluation	non-sensitizing		

Germ cell mutagenicity			
No	Substance name	CAS no.	EC no.
<b>1</b>	<b>titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]</b>	<b>13463-67-7</b>	<b>236-675-5</b>
Type of examination	In vitro mammalian cytogenicity		
Method	OECD 487		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
Route of exposure	oral		
Type of examination	In vivo mammalian somatic cell study: cytogenicity / erythrocyte micronucleus		
Species	rat		
Method	OECD 474		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
<b>2</b>	<b>Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, &lt;2% aromatics</b>	<b>-</b>	<b>918-481-9</b>
Type of examination	in vitro gene mutation study in bacteria		
Species	S. typhimurium TA 1535, TA 1537, TA 98 and TA 100S. typhimurium TA 1535, TA 1537, TA 98, TA 100, TA 102		
Method	OECD 471		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
Route of exposure	oral		
Type of examination	In vivo mammalian somatic cell study: cytogenicity / erythrocyte micronucleus		
Species	mouse		
Method	OECD 474		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
<b>3</b>	<b>propylidynetrimethanol</b>	<b>77-99-6</b>	<b>201-074-9</b>
Type of examination	in vitro gene mutation study in bacteria		
Species	Salmonella typhimurium: TA 1535, TA 1537, TA 98, TA 100; Escherichia coli WP2 uvrA		
Method	OECD 471		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Reproduction toxicity			
No	Substance name	CAS no.	EC no.
<b>1</b>	<b>titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]</b>	<b>13463-67-7</b>	<b>236-675-5</b>
Route of exposure	oral		
NOAEL	>=	1000	mg/kg bw/d
Type of examination	Reproductive studies - one generation		
Species	rat		
Method	OECD 443		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
Route of exposure	oral		
NOAEL	>=	1000	mg/kg bw/d
Type of examination	Prenatal Developmental Toxicity Study		
Species	rat		

Trade name: einzA mix Solid Seidenglanzlack, Basis 1

Product no.: 0069184

Current version : 5.1.2, issued: 03.07.2023

Replaced version: 5.1.1, issued: 14.03.2023

Region: GB

Method	OECD 414		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
<b>2</b>	<b>propylidynetrimethanol</b>	<b>77-99-6</b>	<b>201-074-9</b>
Route of exposure	oral		
NOAEL		2200	ppm
Duration of exposure		19	week/s
Species	rats (male/female)		
Method	OECD 443		
Source	ECHA		

Carcinogenicity			
No	Substance name	CAS no.	EC no.
<b>1</b>	<b>titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]</b>	<b>13463-67-7</b>	<b>236-675-5</b>
Route of exposure	oral		
NOEL		7500	mg/kg bw/d
Species	mouse		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

STOT - single exposure			
No data available			

STOT - repeated exposure			
No	Substance name	CAS no.	EC no.
<b>1</b>	<b>titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]</b>	<b>13463-67-7</b>	<b>236-675-5</b>
Route of exposure	oral		
NOAEL		>	962 mg/kg bw/d
Species	rat		
Method	OECD 408		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
Route of exposure	inhalational		
Species	rat		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
<b>2</b>	<b>Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, &lt;2% aromatics</b>	<b>-</b>	<b>918-481-9</b>
Route of exposure	oral		
NOAEL		>=	500 mg/kg bw/d
Species	rat		
Method	OECD 408		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
<b>3</b>	<b>propylidynetrimethanol</b>	<b>77-99-6</b>	<b>201-074-9</b>
Route of exposure	oral		
NOAEL		67	mg/kg bw/d
Duration of exposure		14	week/s
Species	rats (male/female)		
Source	ECHA		

Aspiration hazard			
No data available			

Delayed and immediate effects as well as chronic effects from short and long-term exposure			

**Trade name:** einza mix Solid Seidenglanzlack, Basis 1

**Product no.:** 0069184

**Current version :** 5.1.2, issued: 03.07.2023

**Replaced version:** 5.1.1, issued: 14.03.2023

**Region:** GB

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage. Ingestion may cause nausea, diarrhoea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

**11.2 Information on other hazards**

**Endocrine disrupting properties**

No data available.

**Other information**

No data available.

**SECTION 12: Ecological information**

**12.1 Toxicity**

Toxicity to fish (acute)			
No	Substance name	CAS no.	EC no.
1	propylidynetrimethanol	77-99-6	201-074-9
LC50	>	1000	mg/l
Duration of exposure		96	h
Species	Alburnus Alburnus		
Source	ECHA		

Toxicity to fish (chronic)			
No data available			

Toxicity to Daphnia (acute)			
No	Substance name	CAS no.	EC no.
1	propylidynetrimethanol	77-99-6	201-074-9
EC50	>	13000	mg/l
Duration of exposure		48	h
Species	Daphnia magna		
Source	ECHA		

Toxicity to Daphnia (chronic)			
No	Substance name	CAS no.	EC no.
1	propylidynetrimethanol	77-99-6	201-074-9
NOEC	>	1000	mg/l
Duration of exposure		21	day(s)
Species	Daphnia magna		
Method	OECD		
Source	ECHA		

Toxicity to algae (acute)			
No	Substance name	CAS no.	EC no.
1	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	13463-67-7	236-675-5
EC50	>	100	mg/l
Duration of exposure		72	h
Species	Raphidocelis subcapitata		
Method	OECD 201		
Source	ECHA		
Evaluation/classification	Based on the available data, the classification criteria are not met.		
2	propylidynetrimethanol	77-99-6	201-074-9
EC50	>	1000	mg/l
Duration of exposure		72	h
Species	Selenastrum capricornutum		

Trade name: einza mix Solid Seidenglanzlack, Basis 1

Product no.: 0069184

Current version : 5.1.2, issued: 03.07.2023

Replaced version: 5.1.1, issued: 14.03.2023

Region: GB

Method	OECD
Source	ECHA

<b>Toxicity to algae (chronic)</b>
No data available

<b>Bacteria toxicity</b>			
No	Substance name	CAS no.	EC no.
1	propylidynetrimethanol	77-99-6	201-074-9
EC50	>	1000	
Duration of exposure		3	h
Species	activated sludge		
Method	EU C.11		
Source	ECHA		

## 12.2 Persistence and degradability

<b>Biodegradability</b>			
No	Substance name	CAS no.	EC no.
1	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	13463-67-7	236-675-5
Source	ECHA		
Evaluation	Not applicable for inorganic substances.		
2	propylidynetrimethanol	77-99-6	201-074-9
Value		100	%
Duration		28	day(s)
Method	OECD 302 B		
Source	ECHA		
Evaluation	readily biodegradable		

## 12.3 Bioaccumulative potential

<b>Bioconcentration factor (BCF)</b>			
No	Substance name	CAS no.	EC no.
1	propylidynetrimethanol	77-99-6	201-074-9
BCF	<	17	
Species	Cyprinus carpio		
Method	OECD 305 C		
Source	ECHA		

<b>Partition coefficient n-octanol/water (log value)</b>			
No	Substance name	CAS no.	EC no.
1	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	13463-67-7	236-675-5
Not applicable			
Source	ECHA		
2	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	-	918-481-9
log Pow		3.17	- 7.22
Method	QSAR		
Source	ECHA		
3	propylidynetrimethanol	77-99-6	201-074-9
log Pow		-0.47	
Reference temperature		26	°C
Method	OECD		
Source	ECHA		

## 12.4 Mobility in soil

No data available.

## 12.5 Results of PBT and vPvB assessment

<b>Results of PBT and vPvB assessment</b>	
PBT assessment	The components of this product are not considered to be a PBT.

Trade name: einza mix Solid Seidenglanzlack, Basis 1

Product no.: 0069184

Current version : 5.1.2, issued: 03.07.2023

Replaced version: 5.1.1, issued: 14.03.2023

Region: GB

vPvB assessment | The components of this product are not considered to be a vPvB.

12.6 Endocrine disrupting properties

No data available.

12.7 Other adverse effects

No data available.

12.8 Other information

Table with 2 rows: Other information, Do not allow to enter drains or water courses.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste code 08 01 11\* waste paint and varnish containing organic solvents or other hazardous substances

The listed waste code numbers, according to the European Waste Catalogue, are to be understood as a recommendation. A final decision must be made in agreement with the regional waste disposal company. Disposal of the product should be carried out in accordance with all applicable regulations following consultation with the responsible local authority and the disposal company in an authorised and suitable disposal facility.

Packaging

Residues must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer. Empty containers must be scrapped or reconditioned.

SECTION 14: Transport information

14.1 Transport ADR/RID/ADN

The product is not subject to ADR/RID/ADN regulations.

14.2 Transport IMDG

The product is not subject to IMDG regulations.

14.3 Transport ICAO-TI / IATA

The product is not subject to ICAO-TI / IATA regulations.

14.4 Other information

No data available.

14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

14.6 Special precautions for user

Transport within the user's premises: Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments

Not relevant

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Table with 2 rows: Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation), According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

Table with 1 row: REACH candidate list of substances of very high concern (SVHC) for authorisation

Trade name: einza mix Solid Seidenglanzlack, Basis 1

Product no.: 0069184

Current version : 5.1.2, issued: 03.07.2023

Replaced version: 5.1.1, issued: 14.03.2023

Region: GB

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

**Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES**

The product contains following substance(s) that are considered being subject to REACH regulation (EC) 1907/2006 annex XVII.

No	Substance name	CAS no.	EC no.	No
1	2-(2-butoxyethoxy)ethanol	112-34-5	203-961-6	75
2	2-methylpentane-2,4-diol	107-41-5	203-489-0	75
3	neodecanoic acid, zirconium salt	39049-04-2	254-259-1	75
4	phosphoric acid	7664-38-2	231-633-2	75
5	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	13463-67-7	236-675-5	75

**Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances**

This product is not subject to Part 1 or 2 of Annex I.

**Directive 2010/75/EU on industrial emissions (integrated pollution prevention and control)**

VOC content	18.53 %
-------------	---------

**Directive 2004/42/CE on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products**

relevant VOC limit value as referred to in Annex II of Directive 2004/42/CE , Cat. : d, type: lb = 300 g/l  
Max. VOC content (limit value) of the product in its ready for use condition = < 300 g/l

**National regulations**

**Other national regulations**

Adhere to national regulations for proper handling and use of hazardous materials. Use appropriate personal protective equipment.

**15.2 Chemical safety assessment**

A chemical safety assessment has not been carried out for this mixture.

**SECTION 16: Other information**

**Sources of key data used to compile the data sheet:**

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

**Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)**

EUH066	Repeated exposure may cause skin dryness or cracking.
H304	May be fatal if swallowed and enters airways.
H351i	Suspected of causing cancer by inhalation.
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.

**Notes relating to the identification, classification and labelling of substances and mixtures ((EC) No 1272/2008, Annex VI)**

V If the substance is to be placed on the market as fibres (with diameter < 3 µm, length > 5 µm and aspect ratio ≥ 3:1) or particles of the substance fulfilling the WHO fibre criteria or as particles with modified surface chemistry, their hazardous properties must be evaluated in accordance with Title II of this Regulation, to assess whether a higher category (Carc. 1B or 1A) and/or additional routes of exposure (oral or dermal) should be applied.

**Trade name:** einza mix Solid Seidenglanzlack, Basis 1

**Product no.:** 0069184

**Current version :** 5.1.2, issued: 03.07.2023

**Replaced version:** 5.1.1, issued: 14.03.2023

**Region:** GB

W	It has been observed that the carcinogenic hazard of this substance arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung. This note aims to describe the particular toxicity of the substance; it does not constitute a criterion for classification according to this Regulation.
1	The concentration stated or, in the absence of such concentrations, the generic concentrations of this Regulation (Table 3.1) or the generic concentrations of Directive 1999/45/EC (Table 3.2), are the percentages by weight of the metallic element calculated with reference to the total weight of the mixture.

#### **Creation of the safety data sheet**

UMCO GmbH

Georg-Wilhelm-Str. 187, D-21107 Hamburg

Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: umco@umco.de

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Alterations/supplements:

Alterations to the previous edition are marked in the left-hand margin.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH.

Prod-ID 653558